

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 500160

PRIMARY CORNER DESCRIPTION N 1/16 Secs 34 & 35

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

| |
|--|
| <p>Burt Holt - For: Sun Studs Inc. - 12/1981 - M90-16 ----- Set - 5/8"x30" iron rod, 25" in the ground, from which: 10" D.Fir bears N.89°30'E(W)., 18.4' mkd: N1/16 S34 BT 11" D.Fir bears S.28°E., 10.6' mkd: N1/16 S35 BT. This cor. Lies on a flat in heavy 2nd growth and Salall brush.</p> |
| <p>Ken Hoffine - For: Lone Rock Timber Co. - May 1991 - M113-9 ----- Found - 5/8" iron rod 0.4 ft. above ground and the following accessories: 14" DF bears S.28°E., 10.6 ft, well healed scar & BLM tag. 11" DF bears N.89°30'W., (rec. N.89°30'E.) 18.4 ft., scribe visible and BLM tag. Corner lies on top of large flat bench ridge top.</p> |
| <p>Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 11/8/2023 - C.S. File 67/57-18 ----- Found - 5/8" Iron rod up 3" 17"x5 ft. burned broken off Fir snag S.32°E., 10.6 ft. (Rec S.28°E.) fully healed single blaze add 3½" mag nail right side center. A fallen 12" Fir out of position, no good root hole, fully healed single blaze. 5/8" iron rod up 4" S.89°39'32"W., 47.32 ft. New - Burnt-sawn 20"x1½ ft. D.Fir stump N.67°E., 11.1 ft. 3½" mag nail top center. Note - Cor. is on top of large flat bench ridge top. Area burnt 9/2020 Compass decl. 14½°E. Oregon Coordinate Reference System Cottage Grove - Canyonville Zone N 222100.453 E 224308.124</p> |
| <p> </p> |