

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 7 Page(s) 2989)

Set yew post 4 ft. long, 4" sq. 24" in the ground for cor. to secs. 22, 23, 26, & 27 marked T24S S23 on NE., R3W S26 on SE., S27 on SW., & S22 on NW faces with 2 notches on S & E edges from which

- A fir, 36" dia. bears N.21°E. 42 lks. mkd: T24S R3W S23 BT
- A fir, 24" dia. bears S.20°E. 43 lks. mkd: T24S R3W S26 BT
- A fir, 24" dia. bears S.51°W. 19 lks. mkd: T24S R3W S27 BT
- A fir, 24" dia. bears N.39°W. 33 lks. mkd: T24S R3W S22 BT

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - Nov. 1967 - C.S. File 54/27-95

-
- Found - Orig. 36" fir, now 42" stump, N.21°E., 27.7 ft., open & find scribe marks.
 - Orig. 24" fir, now burned stump, S.20°E., 28.4 ft., no scribe.
 - Orig. 24" fir, now 30" stump, S.51°W., 12.5 ft., frag. scribe on burned face.
 - Orig. 24" fir, now 24" stump, N.39°W., 21.8 ft., shows scars.

Set - Brass cap at cor. mkd: County Surveyors T24S R3W
Office S 22 | S 23
1967 S 27 | S 26

New BT - 7" D.Fir, N.4°W., 70.0 ft. mkd: T24S R3W S22 CS BT.
No other tree or solid stump.

A 48" Fir stump S.88°E., 32.2 ft. "W" nail & tag

Set - 6' steel fence post alongside brass cap.

Note - This corner lies on very steep west slope.