

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Cor. Secs. 10, 11, 14, & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 7 Page(s) 2950-1)

Set post cor. to secs. 10, 11, 14, & 15. Marked a hemlock 8" dia., for post from which
 A Hemlock, 30" dia., bears N.20°E., 11 lks.
 A Maple, 10" dia., bears S.35°E., 54 lks.
 A Hemlock, 8" dia., bears S.55°W., 13 lks.
 A Cedar, 12" dia., bears N.25°W., 13 lks.

Fd. & used on GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 7 Page(s) 2979)

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - Dec. 1967 - C.S. File 54/27-97

We find no trace of orig. cor. tree or BTs - We do find 2" steel pipe & Weyerhaeuser method BTs as follows:
 16" D.Fir S.17°W., 28.2 ft. "W" nail & tag.
 70" D.Fir, stump N.75°W., 65.9 ft. "W" nail & brass plate & tag.
 48" D.Fir, stump N.3°W., 35.7 ft. "W" nail & brass plate & tag.
 14" Hemlock S.42°E., 38.7 ft. "W" & tag.

Dan Baker, For: Weyerhaeuser Co. - Dec. 8, 1983 - M90-48

Set - 1¾"x36" iron pipe with brass cap with standard markings & "PLS 1978"
 26" fir, N.27°E., 11.3 ft.
 18" hemlock, S.23°E., 45.5 ft.
 23" fir, S.23°W., 43.4 ft.
 58" fir stump, N.20°W., 27.4 ft.
Note- 2" alum. pipe set by Weyerhaeuser Co. bears S.30°27'17"W., 15.50 ft.