

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 7 Page(s) 2986)  
-----  
Set cedar post 3 ft. long, 4" sq., 18" in the ground for ¼ sec. cor. marked ¼ sec. cor. mkd. ¼ S on W face from which  
    A fir, 20" dia., bears N.34°E., 76 lks., mkd: ¼ S BT.  
    A fir, 10" dia., bears S.39°W., 51 lks., mkd: ¼ S BT.

Weyerhaeuser Co., M. D. Hale - 5/3/1963 - C.S. File 53/111-4  
-----  
Found - No orig. BTs found.  
Set - 1"x30" alum. pipe.  
      44" Fir stump, S.39°W., 31.4 ft. with "W" nail & plate.  
      32" Fir stump, N.37°W., 17.0 ft. with "W" nail & plate.  
Note - Area logged.