

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 7 Page(s) 2988)

Set cedar post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ sec. cor. mkd. ¼ S on N face from which
A hemlock, 16" dia., bears N.80°W., 30 lks., mkd: ¼ S BT.
A fir, 20" dia., bears S.54°E., 40 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - March 1968 - C.S. File 54/27-147

Reported as not fd.
Logged & burned - very dense brush.

Steven P. Ness - For: Weyerhaeuser Co. - July 1993 - M117-35

Found - No trace of 1883 GLO monument or accessories.
Set - 2" X 38" iron pipe with 2½" Brass cap cemented to top at proportioned point marked:
T24S R3W
 1 S 26
 4 S 35
 1993 RLS 811
14" D.Fir, N.24°06'E., 44.9 ft. to center, 44.19 ft. to 'W' nail. Scribed "¼ S26 BT"
13" D.Fir, S.50°21'E., 23.2 ft. to center, 22.70 ft. to 'W' nail. Scribed "¼ S35 BT"
14" D.Fir, S.33°09'W., 13.2 ft. to center, 12.47 ft. to 'W' nail. Scribed "¼ S35 BT"
11" D.Fir, N.36°52'W., 48.9 ft. to center, 48.57 ft. to 'W' nail. Scribed "¼ S26 BT"