

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor Secs 25, 26, 35, & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCS0 records Vol. 7 Page(s) 2971)

Set cedar post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 25 & 36, 26 & 35 marked T 24 S S 25 on NE., R 3 W S 36 on SE., S 26 on NW., & S 35 on SW. faces with 1 notch on S & E edges from which
A fir, 24" dia. bears N.50°E. 27 lks. mkd: T24S R3W S25 BT
A fir, 36" dia. bears S.28°E., 9 lks. mkd: T24S R3W S36 BT
A fir, 20" dia. bears S.33°W. 57 lks. mkd: T24S R3W S35 BT
A fir, 40" dia. bears N.50°W. 11 lks. mkd: T24S R3W S26 BT

Doug. Co. Surveyors Office - V.R.Tracy - 3/1968 - C.S. 54/27-147

Unrecorded ren. at sec. cor?
Found - 1½" IP & 8' mkr. pipe & "W" method BTs.
46" Fir stump S.30°E., 6.5 ft. "W" nail & tag.
44" Fir stump N.46°W., 7.2 ft. "W" nail & tag.
36" Fir stump N.60°E., 18.2 ft. "W" nail & tag.
52" Fir stump S.50°W., 55.7 ft. "W" nail & tag. No scribe fd.

Steve Ness - For: Weyerhaeuser Co. - July 1993 - M 117-35

Found - 1½" Iron Pipe.
30" D.Fir stump, N.58°55'E., 19.5 ft. to center, 18.02 ft. to 'W' nail, (N.60°E., 18.3 ft.)
38" D.Fir stump, S.28°10'E., 8.3 ft. to center, no measure to 'W' nail, (S.34°E., 6.5 ft.)
48" D.Fir stump, S.52°10'W., 61.6 ft. to center, 60.68 ft. to 'W' nail, (no record of this stump on Weyco report)
42" D.Fir stump, N.44°15'W., 9.1 ft. to center, 7.42 ft. to 'W' nail, (N.46°W., 7.2 ft.)
Set - Cemented a 2½" Brass Cap to top of found 1½" iron pipe marked:
T24S R3W
S26 | S25
S35 | S36
1993 RLS 811
15" D.Fir, N.36°17'E., 27.1 ft. to center, 26.27 ft. to 'W' nail. Scribed "T24S R3W S25 BT"
14" D.Fir, S.48°26'E., 28.3 ft. to center, 27.36 ft. to 'W' nail. Scribed "T24S R3W S36 BT"
16" D.Fir, S.49°45'W., 23.9 ft. to center, 23.13 ft. to 'W' nail. Scribed "T24S R3W S35 BT"
16" D.Fir, N.26°14'W., 40.2 ft. to center, 39.29 ft. to 'W' nail. Scribed "T24S R3W S26 BT"

Cont.

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor Secs 25, 26, 35, & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 11/10/2021 (Filed 4/7/2022) - C.S. File 67/51-32

Found - 1½" I.D. iron pipe, proj. 21", brass cap missing.
1968 BTs-30" D.Fir stump N.58°55'W., 19.5 ft. burnt to ground
36"x3 ft burnt D.Fir stump D.Fir stump S.28°10'E.,
8.3 ft.

34"x3 ft burnt D.Fir stump S.52°10'W., 61.6 ft.
28"x2½ ft. burnt D.Fir stump N.44°15'W., 9.1 ft.
No trace of W nails

1993 BTs-22"x12' D.Fir N.36°17'E., 27.3 ft (rec. 27.1 ft.)
21"x2' burnt D.Fir stump S.48°26'E., 28.3 ft.
21"x5' burnt D.Fir stump S.50°W., 23.8 ft (rec
S.49°45'W., 23.9 ft) to mag nail RSC
22"x9' sawn D.Fir stump N.26°14'W., 40.5 ft. (Rec.
40.2 ft) to mag nai. RSC

New - Drove pipe to project 8". Built rough stone mound
around base.
21"x4' burnt Fir stump N.71½°E., 32.5 ft. 4" mag
nail top center.

Note - See sketch in file
Compass decl. 14½°E.

Lat: 43°26'42.94 N Long: 123°00'44.15" W