

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Cor. Secs. 13, 14, 23, & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 7 Page(s) 2949)

Set post cor. to secs 13, 14, 23, & 24 from which
A dogwood, 7" dia., bears N.65°E., 27 lks.
A hemlock, 18" dia., bears S.12°E., 38 lks.
A hemlock, 5" dia., bears S.10°W., 13 lks.
A yew, 6" dia., bears N.53°W., 25 lks.

FD & used on GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 7 Page(s) 2976)

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - March 1968 - C.S. File 54/27-141

Found - 1" IP 4 ft. above ground set for cor. & Weyerhaeuser method BT.
42" D.Fir stump N.68°E., 21.6 ft. with "W" nails & tags.
Unrecorded
Probably orig. BT for SE quad down & out of position - we are unable to determine the exact location of this BT due to logging. We do find scribe mks. on this tree - no trace any other OBTS - The orig. creek calls would fit good.
Note - We do not renew.

Dan Baker, Peel Baker Land Surveying - For: Weyerhaeuser Co. Dec. 8, 1983 - M 90-48

Found - 1¼" iron pipe approx. 4 ft. high
50" fir stump, N.68°E., 21.6 ft. (dist. to "W" nail)
14" rotten hemlock stub (down) S.10°E., 25.1 ft. (from center of uproot hole) (Old Weyer. Co. tag - scribing once visible see notes of V.R. Tracy, Doug. Co; C.S. 54/27)

Set - Drove in iron pipe to 16" above ground & cemented in brass cap.
10" Fir, N.29°E., 7.4 ft.
12" Fir, S.35½°E., 28.8 ft.
12" Fir, S.72½°W., 18.1 ft.
12" Fir, N.53½°W., 37.4 ft.