

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor Secs 11, 12, 13, & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCS0 records Vol. 7 Page(s) 2977)

Set cedar post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 11, 12, 13, & 14 marked T 24 S S 12 on NE., R 3 QW S 13 on SE., S 14 on SW., & S 11 on NW. faces with 4 notches on S & 1 notch on E edges from which
A fir, 24" dia. bears N.29°E. 43 lks. mkd: T24S R3W S12 BT
A fir, 20" dia. bears S.52°E. 51 lks. mkd: T24S R3W S13 BT
A fir, 36" dia. bears S.17°W. 21 lks. mkd: T24S R3W S14 BT
A fir, 18" dia. bears N.37°W. 34 lks. mkd: T24S R3W S11 BT

Marion D. Hale, Weyerhaeuser - 3/26/1954 - C.S. 53/111-17

Found - Cedar post gone
24" Fir, N.29°E., 43 lks., snag stump.
Rec. 36" Fir, S.17°W., 21 lks., now 56" Fir S.17°E., (not West) 21 lks., is scribed on bark, marked S13 T24 R3 BT.
18" Fir, N.37°W., 34 lks., snag stump.
Set - Stake for corner.
20" Cedar snag, S.47°W., 7.3 ft., "W" nail & plate.
48" Fir, N.11°W., 33.2 ft., "W" nail & plate.
58" Fir N.47°E., 66.5 ft., "W" nail & plate.

Dan Baker, Peel Baker Land Surveying - For: Weyerhaeuser Co. Dec. 8, 1983 - M 90-48

Found - 58" fir stump, N.50°E., 66.5 ft. (dist. to "W" nail)
11" hemlock stump, S.33°E., 30.7 ft. (dist. to "W" nail)
42" fir stub, S.50½°W., 48.2 ft. (dist. to "W" nail)
43" fir stump (20' high) N.10°W., 33.2 ft. (dist. to "W" nail)
Orig. sec. 13 BT (bark scribed) uprooted & slid downhill, center of roots S.17°E., 13.9 ft. (rec. S.17°W.)
Set - 2"x36" iron pipe with brass cap mkd. with standard markings & "PLS 1978"

Douglas Co. Surveyors Office - Crew: Stephen Flaue & Jeff Lorsung- 10/17/2024 - C.S. File 67/59-9

Found - Brass cap on 2" iron pipe up 2"
Fir stump 58"x4 ft. S.48°E., 68.5 ft. (Rec. N.50°E., 66.5 ft. to face) add 3½" mag nail top center.
Root hole S.50½°W., 48.2 ft.
Root hole S.17°E., 13.9 ft. Continued next page

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor Secs 11, 12, 13, & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New - Sawn Fir stump 19"x1½ ft. N.64°E., 9.4 ft. 3½" mag
nail top center.

Sawn Fir stump 22"x2 ft. S.35°W., 18.0 ft. 3½" mag
nail top center.

Note - Area burnt 9/2020
Compass decl. 14¼°E.

Oregon Coordinate Reference System

Cottage Grove - Canyonville Zone

N 1239630.754 E 249566.359