

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 7 Page(s) 2980-1)

Set cedar post 4 ft. long, 4" sq. 24" in the ground for cor. to secs. 1, 2, 11, & 12 marked T24S S1 on NE., R3W S12 on SE., S11 on SW., & S2 on NW faces with 5 notches on S & 1 notch on E edges from which

- A fir, 30" dia., bears N.16°E., 19 lks., T24S R3W S1 BT
- A fir, 20" dia., bears S.72°E., 54 lks., T24S R3W S12 BT
- A fir, 24" dia. bears S.38°W. 55 lks. mkd: T24S R3W S11 BT
- A hemlock, 10" dia., bears N.41°W., 35 lks., mkd: T24S R3W S2 BT.

Douglas Co. Surveyors Office - V.R. Tracy - Nov. 1967 - C.S. File 54/16-26A

Not found.
Logged & burned.