

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36; 30 & 31, T24-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 7 Page 2947)

Set post cor. to secs. 25, 30, 31 and 36, from which

- A Hemlock 24" dia., bears N.60°E., 24 lks. dist.
- A Hemlock 18" dia., bears S.25°E., 10 lks. dist.
- A Hemlock 14" dia., bears S.25°W., 14 lks. dist.
- A Spruce 30" dia., bears N.72°W., (?) dist.

BLM resurvey by Levi E. Tallett and C. Albert White, Cadastral Surveyors, under Group #294, Surveyed May 1951/Aug. 1963 - (DCSO records Vol. 32 Page(s) 13287-88)

The Sec. Cor. determined at record distance from the old SE. and SW. bearing trees:

- A Hemlock stub 18" dia., bears S.26°45'E., 10 lks. dist., blaze healed. (Rec. brg. S.25°E.)
- A fallen Hemlock 18" dia., bears S.41½°W., 24 lks. dist., edge of face of old blaze under 78 years overgrowth. (Rec. brg. S.25°W.)
- A dead Fir 22" dia., bears N.63¼°W., 22 lks. dist., with partial scribe marks on old bark blaze. (Rec. a Spruce, 30" dia., bears N.72°W., no dist. given.)

At the corner point

Set an iron post, 36" long, 2" dia., 22" in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd:

T 24 S
R 3 W R 2 W
S 25 S 30
S 36 S 31
1951

from which

- A Fir 24" dia., bears N.82°E., 72 lks. dist. mkd. T24S R2W S30 BT.
- A Fir 24" dia., bears S.26½°E., 143 lks. dist. mkd. T24S R2W S31 BT.
- A sawed Fir stump 32" dia., bears S.50½°W., 52 lks. dist. mkd. T24S R3W S36 BT.
- A Fir 22" dia., bears N.41¼°W., 23 lks. dist. mkd. T24S R3W S25 BT.

Weyerhaeuser Co. - Date of survey Sept. 1955 - Filed with DCSO July 1960 - C.S. File 42/323

Found evidence of the original GLO corner, but did not reference.

continued next page

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36; 30 & 31, T24-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

David Edwards - Brant Miller, Party Chief - Eric Sprinkle,
Witness - 6/1/2012 - C.S. File 65/76-59

Found - 1951 BLM brass capped iron pipe in mound of stones.
35" dia., fir stump bears N.82°E., 47.5 ft.
34" dia., fir stump bears S.26½°E., 94.4 ft.
The fir N.41¼°W., 15.2 ft. is a windfall.
New - 9" dia., Fir bears N.37°E., 14.5 ft. scribed "T24S
R2W S30 BT"
An 8" dia., Hemlock bears S.82°E., 22.9 ft. scribed
"T24S R2W S31 BT"
An 11" dia., Cedar bears S.25°W., 9.5 ft. scribed
"T24S R3W S36 BT"
A 6 ft. steel post is set 2 ft. west.
Note - Dec. 18°E