

PRIMARY CORNER DESCRIPTION Sec Cor for 13 & 24; 18 & 19, T24-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 7 Page(s) 2948)

-----  
 Set post cor. to secs. 13, 18, 19 and 24, from which  
 A Cedar 20" dia., bears N.82°E., 23 lks. dist.  
 A Hemlock 20" dia., bears S.70°E., 35 lks. dist.  
 A Cedar 30" dia., bears S.30°W., 40 lks. dist.  
 A Hemlock 10" dia., bears N.45°W., 10 lks. dist.

Donald H. Jordan - For: Weyerhaeuser Co. - Oct. 8, 1965  
 (Filed March 1966) - C.S. File 53/111-33

-----  
 Found - 30" now 44" Cedar S.29°W., 24.8 ft., face grown over, no scribing.  
 10" now 13" Hemlock N.45°W., 6.6 ft., face open, rotten, scribing visible.  
 20" now 42" Cedar N.82°E., 15.2 ft., face grown over, no scribing.  
 20" now 32" Hemlock S.70°E., 23.1 ft., tree windthrown, face closed.  
 Set 1" x 30" alum. pipe, from which  
 Orig. 42" Cedar N.83°E., 13.6 ft. "W" nail & plate.  
 Orig. 44" Cedar S.29°W., 24.0 ft. "W" nail & plate.  
 36" Hemlock N.88°W., 25.3 ft. "W" nail & plate.  
 68" Fir N.28°E., 35.9 ft. "W" nail & plate.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew  
 March 1968 - C.S. File 54/27-139

-----  
 Found - 1" x 30" alum. pipe and BTs recorded by W. Co. Pipe bent over under log.  
 Orig. 30" now 44" Cedar S.30°W., 26.4 ft., axe notch on reverse face (Rescribed "T24S R3W S24 CS BT")  
 Orig. 20" now 42" Cedar N.82°E., 15.2 ft., open and find "B" scribe. (Rescribed "T24S R2W S18 CS BT")  
 No trace of orig. NW. BT. SE. BT, down.  
 36" Hemlock stump, N.88°W., 25.3 ft. to "W" nail, we mark "T24S R3W S13 CS BT"  
 68" D.Fir stump N.28°E., 35.9 ft. to "W" nail.

This area clear cut, no live trees.  
 Set brass cap at cor. mkd. County Surveyors Office 1968  
 (Reset alum. pipe alongside)

|   |      |      |   |
|---|------|------|---|
| R | T 24 | S    | R |
| 3 | S 13 | S 18 | 2 |
| W | S 24 | S 19 | W |

This corner lies 20 ft. S. of cat logging road, course NW.