

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 - (DCSO records Vol. 7 Page(s) 2961)

Set a Cedar post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 7, 12, 13, 18 marked T24S S7 on NE.; R2W S18 on SE.; R3W S13 on SW.; and S12 on NW. faces, with 2 notches on N. and 4 notches on S. edges, from which
A Maple 12" dia., bears N.15°E., 40 lks. dist. mkd. T24S R2W S7 BT.
A Fir 36" dia., bears S.50°E., 16 lks. dist. mkd. T24S R2W S18 BT.
A Maple 12" dia., bears S.40°W., 10 lks. dist. mkd. T24S R3W S13 BT.
A Fir 16" dia., bears N.45°W., 37 lks. dist. mkd. T24S R3W S12 BT.

Donald H. Jordan - For: Weyerhaeuser Co. - March 1966 - C.S. File 53/111-32

Found - 38" Fir N.40°W., 24.4 ft., slide, no evidence.
14" Maple N.15°E., 27.2 ft., stub 5 ft. high, "W" nail but no scribing.
52" Fir S.77°E., 47.5 ft., windthrow root wad * dist., no reference.
34" Fir S.59°W., 33.0 ft., slide no evidence.
Set 1¼" x 42" Iron pipe, from which
14" Maple stub, N.15°E., 27.2 ft. (orig. BT) "W" nail and plate.
36" Fir stump, N.56°W., 37.2 ft. "W" nail and plate.
6/10/1970 WEYCO report C.S. 53/110-19: 3 Fir BTs (N.56°W., 37.2 ft; S.74°W., 28.4 ft; S.49°E., 88.0 ft now stumps. All 3 with "W" nail and plates) added 11/17/2020

DCSO by V. Tracy - March 1968 - C.S. File 54/27-138
Not enough evidence to renew. We could not find any scribe in Maple, called original.