TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 700540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 12; & 7, T24-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 - (DCSO records Vol. 7 Page(s) 2962)

Set Dogwood post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ S. on W. face, from which

A Hemlock 24" dia., bears N.40°E., 30 lks. dist. mkd. ¼ S BT.

A Vine Maple 5" dia., bears S.45°W., 29 lks. dist. mkd. ¼ S BT.

Weyerhaeuser Company - 1958-1961-1964 - C.S. File 53/110-

Found - 24" Hemlock N.40°E., 19.8 ft, now windfall.
Estimated orig. position of Hemlock windfall and set a point on a log for corner from orig. notes.
No trace of 5" Vine Maple, S.45°W., 19.1 ft.

No corner set, log at place for corner.

New BTs- 14" Hemlock S.61°E., 60.2 ft. "W" nail and plate
62" Fir N.57°W., 102.9 ft. "W" nail and plate.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew March 4, 1968 - C.S. File 54/27-137

Found - 1" alum. pipe set at corner.
14" Hemlock now stump, S.61°E., 60.2 ft. with "W" nail and tag.
62" Fir now stump, N.57°W., 112.0 ft. (Rec. 102.9 ft.) with "W" nail and tag. Dist. on tag changed since being recorded.
Orig. 24" now 34" Hemlock, down, N.40°E., 19.8 ft. previously opened and shows scribe.

Set Brass cap at cor. mkd: (Reset alum. pipe alongside)

County Surveyors Office
R 3W | T 24 ¼ S 12 1968 | S 7 R 2W

New BTs- 11" Hemlock N.11½°E., 54.2 ft. mkd. "¼ S12 CS BT"
11" Hemlock stump N.68°W., 19.2 ft. mkd. ¼ S12 CS BT

Corner lies 10 ft. S. of old cat logging road in cut off area.