

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 038010

PRIMARY CORNER DESCRIPTION NE Cor. Langley Hall DLC 38

Alias 046020 Description NW Cor James Henry Smith DLC 46
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

DLC Survey by - Dennis Hathorn, under contract dated Sept 1856 (DCSO DLC records Pg 146)

Set post - from which
An Oak, 24" dia., bears S.10°W., 54 lks.
An Oak, 15" dia., bears N.78°E., 166 lks.

Douglas Co. Surveyors Office -Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy - Mike Stone - June 1963 - C.S. File 53/9-55

Looked for and not found.

BLM dependent resurvey by James E. Jelly, Cadastral Surveyor, under Group #979, surveyed May/Sept. 1979 (DCSO records Vol. 42 Page(s) 16411)

The NW cor. of DLC #46, identical with the NE cor. of DLC #38, monumented with an iron rod, of which I have no record, 2" dia., firmly set, projecting 2" above ground. This position is harmoniously related to existing orig. corners, and is accepted as the best available evidence of the position the orig. corner.

At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

T24S R4W
S 15

DLC 38 | DLC 46
1979

from which
An Oak, 10" dia., bears S.82¼°E., 61 lks., mkd: C 46 BT.
A Fir, 5" dia., bears S.45 3/4°W., 91 lks., mkd: C 46 BT.
Reset iron rod alongside iron post.