TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 040060

PRIMARY CORNER DESCRIPTION ESE Cor. Wm. Hanna DLC #40

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

DLC Survey by - Dennis Hathorn, under contract dated Sept 1856 (DCSO DLC records Pg 149)

Set post for cor. - from which
An Oak, 12" dia., bears N.50°E., 32 lks.
An Oak, 24" dia., bears N.30°W., 200 lks.

Douglas Co. Surveyors Office -Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy - Mike Stone - April 1963 - C.S. File 53/9-51

Found - W.Oak, now 24" N.50°E., 21.1', cut open & fd. good scribing "BT". Tree in good condition.
Rotten remains of large Oak, N.30°W., 132.0', too far gone to find scars or scribing.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS OFFICE 1963
T24S R4W E SE DLC 40 _____
14" W.Oak, S.65°W., 24.1', mkd: E SE DLC 40 CS BT.
12" W.Oak, S.2°W., 31.2', mkd: E SE DLC 40 CS BT.

Douglas Co. Surveyors Office - Stephen J Flause - Mike Koch - 2/20/2015 - C.S. File 67/42-11

Found - 1963 2½" dia., brass cap (properly mkd) on a 1" I.D. iron pipe is firmly set protruding 12" above ground.
An oak 12" dia., now a 30" dia., W.Oak with partially healed, previously opened blazes (no visible scribing); bears N.50°E., 21.1 ft. (as per record) OBT
No evidence of other OBT remains.
A 12" W.Oak now a double trunk W.Oak the most Northerly 17" dia., trunk of which has a fully healed double blaze. The C.R.C. of this tree bears S.03½°W., 32.0 ft. (record of S.2°W., 31.2' is to scribed trunk) 1963
A 14" W.Oak, now a 20" dia., W.Oak with a fully healed double blaze; bears S.66½°W., 24.1 ft. (rec. S.65°W., (bearing to blaze) 24.1') 1963
C.R.C. = center root collar

New - An 18" dia., B.Oak scribed "ESE DLC 40" "CSBT" on a double blaze; bears N.46½°W., 75.1' ft.

Note - Monument is on gentle south slope in open wood mainly of oak and hawthorn with some fir and madrone.
Compass decl. 15¼°E.