

PRIMARY CORNER DESCRIPTION NW Cor Samuel Driver DLC #41

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

DLC Survey by - Dennis Hathorn, under contract dated Sept 1856 (DCSO DLC records Pg 150)

Set post for cor. - from which
 An Oak, 12" dia., bears S.53°W., 227 lks.
 An Oak, 18" dia., bears S.63°W., 230 lks.

Douglas Co. Surveyors Office - C.E. Roberts, Co. Surveyor - Aug. 1904 - FB 9 Pg 1

W.Oak, 6" dia., bears N.45°W., 37 lks.
 W.Oak, 5" dia., bears S.87°W., 33 lks.

Gene Richardson & Edwin Woodford - 1945 - No record source found.

Set - A 2" x 30" I.P. - reset from 2 old bearing trees.
 Marked the following new BT:
 10" W.Oak, S.67°30'E., 31.6'.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy - Mike Stone - Feb/March 1963 - C.S. File 53/9-43

Found - 2" Iron pipe at cor. as set by Woodford & Richardson, 1945.
 14" W.Oak, S.67½°E., 31.6', shows very plain axe scar. 1945
 Orig. 12" W.Oak, now 15" S.53°W., 149.8', scribing visible.
 Orig. 18" W.Oak, now 36", S.63°W., 151.8', shows good scar.
 No trace of either tree marked by Roberts in 1904.
 New BT - 13" B.Oak, North 6.5' mkd: NW DLC 41 CS BT
 Corner is in fence corner, fences East, West & South.

Douglas County Surveyors Office - Randall Smith & Stephen Flause - 2/20/96 - C.S. 64/66-11

Found - 2" I.D. Iron pipe protruding 6" above ground.
 No positive evidence of O.B.T.s or evidence of BT's from 1904 Ren. found.
 14" dia. W.Oak, with a fully healed double blaze, bears S.70°E., 31.6', to root crown.
 18" dia. 2' high Oak stump, with a healed blaze, bears North 6.5'.
 (Cont. next page)

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 041020

PRIMARY CORNER DESCRIPTION NW Cor. Samuel Driver DLC #41

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- 6" dia. I.Cedar, double blazed and scribed "NW DLC 41 CS BT", bears N.8°E., 14.9'.
6" dia. D.Fir, double blazed and scribed "NW DLC 41 CS BT", bears N.77½°W., 34.6'.
14" dia., D.Fir, single blazed and scribed "NW DLC 41 CS BT", bears S.82°W., 4.2'.
corner lies at the intersection of south and east running fence lines.