TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 18 & 19

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855 (DCSO records Vol. 7 Page(s) 3051)

Set ¼ sec. post from which
A W.Oak, 12" dia., bears S.73°W., 131 lks.
A W.Oak, 15" dia., bears N.28°W., 162 lks.

Douglas Co. Surveyors Office - James Byron - Milo Godfrey & Clete Putman - April 1959 - C.S. File 49/124-43

Found - Orig. 12", now 24" W.Oak, S.73°W., 86.5', this BT opened years ago. I open near base & find faint scribe marks "T C"
No trace of orig. NW BT, falls at bank of creek, may have washed out.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS OFFICE 1959 T24S R4W ¼ S18/S19
33" W.Oak, bears S.68°W., 88.6', scribed ¼ S19 CS BT
12" W.Oak, bears N.33°W., 54.2', scribed ¼ S18 CS BT
See sketch in file.

Fd. Ok by B. Shaner, 9/9/1988 - CS File 63/85-8

Douglas Co. Surveyors Office - Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - April 11, 1989 - C.S. File 62/63-7

Found - 1959 2½" dia., DCSO brass cap on a 1½" O.D. iron pipe protruding 9" above ground.
12 now 24" dia., 2' high burnt out Oak stump with evidence of a previously opened blaze, no scribing or axe marks visible, bears S.73°W., 86.5'. Orig. BT
33" now 37" dia, W.Oak, w/fully healed double blaze bears S.69½°W., 88.6' (Rec. S.68°W., 88.6') 1959
A double trunked W.Oak with a fully healed double blaze fd. on 12" now 15" dia., southeast trunk, bears N.33°W., 54.8', (rec. N.33°W., 54.2' dist. is to center of southeast trunk) 1959
New BT - 10" dia., W.Oak double blazed and scribed "¼ S18 CS BT" bears N.10°E., 7.6'.

Found OK by R. Brown, July 2001 - 2001-0075
Fd. BC by D. Edwards, 1/2007 - 2007-0062A&B