

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor Secs 7, 8, 17, & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855
(DCSO records Vol. 7 Page(s) 3052)

Set cor. post from which
A B.Oak, 24" dia., bears N.69°W., 55 lks.
A B.Oak, 10" dia., bears S.55°W., 93 lks.
A B.Oak, 30" dia., bears N.78°E., 353 lks.
A W.Oak, 10" dia., bears S.77°E., 146 lks.

Douglas Co. Surveyors Office -Milo E. Godfrey, Deputy Co.
Surveyor - Vernon Tracy - Mike Stone - March/April 1963 -
C.S. File 53/9-45

Found - 32" B.Oak dead but standing N.69°W., 36.3', cut open
& found good scribing "24"
Oak, down & rotting S.55°W., 61.4', fd. good
scribing "S1"
Oak stump, pushed out of position, S.77°E., 96.4',
good reverse scribing.
Oak, down 7 rotting, N.78°E., 233.0', lying face
down, did not open.
Scribed wooden stake hanging in fence line, just
East of corner.
Set - Brass cap at cor mkd: COUNTY SURVEYORS OFFICE 1963
T24S R4W S 8 | S 7
S18 | S17
14" W.Oak, S.56°E., 24.0', mkd: T24S R4W S17 CS BT.
7" W.Oak, N.62°E., 7.2', mkd: T24S R4W S8 CS BT.
7" D.Fir, S.52°W., 28.4', mkd: T24S R4W S18 CS BT.
9" D.Fir, N.52°W., 35.2', mkd: T24S R4W S7 CS BT.
A N& S fence line bears East 3' from corner.