

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855
(DCSO records Vol. 7 Page(s) 3055)

Set ¼ sec. post from which
 A B.Oak, 30" dia., bears S.65°E., 37 lks.
 A B.Oak, 18" dia., bears S.67°W., 10 lks.

Fd & used in Retracement survey - Oscar F. Thiel, Contract #658, May 1896 (DCSO records Vol. 7 Page(s) 3080)

BLM dependent resurvey by C Albert White & Norman J McDonald, cadastral surveyors, under Group #s 243, 350, & 513, surveyed April/July 1963 (DCSO records Vol 32 Page 13472)

The ¼ sec. cor. of secs. 5 & 6, determined at record bearing and dist. from the remains of the orig. BTs:
 An Oak snag, 30" dia., bears S.65°E., 37 lks., with a burned blaze.
 An Oak stump hole, bears S.67°W., 10 lks.
At the corner point
Set an iron post, 20" long, 2½" dia., 21" in the ground, with brass cap mkd:
 ¼
 S6 | S5
 T24S | R4W
 1963
from which new BTs:
 A Fir, 8" dia., bears East, 80 lks., dist. mkd: ¼ S5 BT.
 A Fir, 12" dia., bears S.32°W., 196 lks., mkd: ¼ S6 BT.

Found OK by T. Baker, Jan. 2001 - 2001-0016 A & B

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Survey Tech, under special instructions and Group No. 2210, surveyed Oct./Nov. 2008 - (DCSO records Vol. 57 Page(s) 22360)

The ¼ sec. cor. of secs. 5 and 6, monumented with an iron post, 2½" dia., firmly set, projecting 7" above the ground, with brass cap (properly) mkd.
from which the remains of a BT mkd. by White and McDonald
 A fir snag, 12" dia., bears S.33°W., 132.0 ft., with a healed blaze. (Record, S.32°W., 129.4 ft.)
and new bearing trees
 A fir, 8" dia., bears S.81¾°E., 296.7 ft., mkd. ¼ S5 BT.
 A fir, 10" dia., bears S.54½°W., 55.7 ft., mkd. ¼ S6 BT.
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.
continued next page

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

The geographic position (NAD 1983 (CORS)) of the ¼ section corner of sections 5 and 6, as determined by direct occupation utilizing dual frequency carrier phase GPS receivers, relative to National Spatial Reference System (NSRS) Continuously Operating Reference Station (CORS) "DODSON BUTTE CORS ARP" and National Cooperative CORS Network Station "ROSEBURG COOP CORS ARP", is as follows:
Latitude: 43°30'41.754"N Longitude: 123°12'25.787"W

Fd. as per record, N Hibbs - 1/2025 - M185-22