

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 32

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855  
(DCSO records Vol. 7 Page(s) 3048)

-----

Set 1/4 sec. post from which  
A B.Oak, 8" dia, bears N.16°E., 30 lks.  
A W.Oak, 8" dia., bears S.30°E., 90 lks.

Douglas Co. Surveyors Office - F.C. Frear, Dep. Co. Surveyor  
- Witness: Alva Manning and Harrison Manning - Feb. 1917 -  
FB 43 Pg 52

-----

Renew from old BT  
Set in a 8"x10"x24" sandstone from which  
A B.Oak, bears N.16½°E., 30 lks.  
A W.Oak, bears S.28 3/4°E., 90 lks  
A Fir, 10" dia., bears N.65 3/4°E., 5 lks.

Douglas Co. Surveyors Office -Milo E. Godfrey, Deputy Co.  
Surveyor - Vernon Tracy - Mike Stone - May 1963 - C.S. File  
53/9-85

-----

Found - Rock set by Frear, "X" cut in top.  
20" Fir stump, N.65 3/4°E., 3.3', bottom of axe face  
only, no scribing.  
Stump hole & rotten Oak log S.30°E., 59.4', opened  
& found good reverse scribing "B". Upper face  
rotted away (orig. BT)  
Stump hole only N.16°E., 19.8'.  
Set - Brass cap alongside rock mkd: COUNTY SURVEYORS T24S  
R4W 1/4 S29/S32 OFFICE 1963  
10" W.Oak, S.40°E., 50.8', mkd: 1/4 S32 CS BT.  
6" W.Oak, N.75°E., 51.3', mkd: 1/4 S29 CS BT.  
Note - Corner lies on East slope, approx. 100' W. of small  
stream flowing south.

Fd. & used in BLM dependent resurvey by James E. Jelly,  
Cadastral Surveyor, under Group #979, surveyed May/Sept. 1979  
(DCSO records Vol. 42 Page(s) 16404)

FD. BC 11/1992 M. Heimbürger M 116-18.  
Fd. OK 1/23/1996 by H. Christensen - M123-36.