

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855  
(DCSO records Vol. 7 Page(s) 3049)

-----

Set ¼ sec. post from which  
A W.Oak, 12" dia., bears N.45°E., 53 lks.  
A W.Oak, 12" dia., bears S.51°W., 152 lks.

Douglas Co. Surveyors Office -Milo E. Godfrey, Deputy Co.  
Surveyor - Vernon Tracy - Mike Stone - May 1963 - C.S. File  
53/9-17

-----

No trace of cor. or BTs fd.

BLM dependent resurvey by James E. Jelly, Cadastral Surveyor,  
under Group #979, surveyed May/Sept. 1979 (DCSO records Vol.  
42 Page(s) 16407)

-----

The ¼ sec. cor. determined at record bearing & dist. from the  
remains of an orig. BT;  
An Oak stump 20" dia., bears N.45°W., 53 lks., with scribe  
marks BT in reverse and relief visible on overgrowth.  
At the corner point  
Set an iron post, 28" long, 2½" dia., 24" in the ground, with  
brass cap mkd: T24S R4W  
¼  $\frac{S \ 20}{S \ 29}$   
1979

from which new BTs  
A W.Oak, 9" dia., bears N.43°E., 84 lks., mkd: ¼ S20 BT.  
A W.Oak, 13" dia., bears S.54°W., 50 lks., mkd: ¼ S29 BT.

Fd. BC 11/1992 by Mark Heimbürger - M 116-18.  
Fd. Ok 1/1996 by H. Christensen - M 123-36.  
Found OK by R. Brown, July 2001 - 2001-0075