

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 240640

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Survey Tech, under special instructions and Group No. 2210, surveyed Oct./Nov. 2008 - (DCSO records Vol. 57 Page(s) 22358)

Point for the center 1/4 sec. cor. of sec. 5, at intersection with the E and W centerline.

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

T24S R4W
C ¼
S 5
2008

from which

An oak, 15" dia., bears N.82¾°E., 43.3 ft., mkd. C¼ S5 BT.

A fir, 6" dia., bears S.26¼°E., 47.0 ft., mkd. C ¼ S5 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor., a point established by the BLM, Roseburg District Office, in 1978, in the course of an unofficial administrative survey, bears N.70°37'42"W., 1.16 ft., monumented with a steel fence post, 1" dia., firmly set, projecting 25" above the ground, and is not utilized in the course of this survey.