

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 5; & 32, T23-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and bearing trees mkd. by person(s) unknown
An oak, 15" dia., bears S.47°E., 7.6 ft., with a healed blaze.

An oak, 20" dia., bears S.57¼°W., 13.3 ft., with a healed blaze.

and a new bearing tree

A fir, 6" dia., bears S.70°E., 30.8 ft., mkd. ¼ S5 BT.
Each new bearing tree has a 2½"x¼" magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

The geographic position (NAD 1983 (CORS)) of the ¼ section corner of sections 5 & 32, on the North boundary of the township, as determined by a tie from a temporary GPS control point, established utilizing dual frequency carrier phase GPS receivers, relative to NSRS CORS "DODSON BUTTE CORS ARP" and National Cooperative CORS Network Station "ROSEBURG COOP CORS ARP", is as follows:

Latitude: 43°31'08.25"N. Longitude: 123°11'49.07"W.