



TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor. Secs 28, 29, 32, & 33

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A W.Oak, 50" dia., bears N.25°E., 420 lks., with scribe marks R4W visible on open blaze.  
and BTs mkd. by Byron  
A B.Oak, 30" dia., bears N.38½°E., 372 lks., with healed blaze.  
A W.Oak, 18" dia., bears N.83½°E., 385 lks., with healed blaze.  
and bearing objects recorded by Tracy  
The SE corner of porch roof support of a concrete block house, bears N.4°E., 126 lks.  
The NW corner of the house, bears N.18°W., 167 lks.  
At the corner point  
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:  
T24S R4W  
S 29 | S 28  
S 32 | S 33  
1979  
Invert county iron post & reset alongside iron post.  
No other suitable accessories available within the limits.  
Corner is located on ridge, bears N.30°E., & S.30°W.