

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor Secs 20, 21, 28, & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855
(DCSO records Vol. 7 Page(s) 3044)

Set post cor. from which:
A B.Oak, 12" dia., bears S.11°E., 70 lks.
A B.Oak, 12" dia, bears N.53°E., 115 lks.
A B.Oak, 10" dia., bears N.34°W., 56 lks.
A W.Oak, 15" dia., bears S.82°W., 218 lks.

Douglas Co. Surveyors Office - James Byron - Milo Godfrey &
Clete Putman - May 1960 - C.S. File 49/124-45

Found - Orig. 15" now 30" W.Oak, S.82°W., 143.9'. I open &
find good scribe marks. No trace of other BTs fd.
Set - Brass cap at cor. mkd: COUNTY SURVEYOR'S OFFICE, 1960
S20|S21 T24S R4W
S29|S28
7" R.Fir, bears N.80°E., 8.5', scribed S21 T24S R4W
CS BT.
7" W.Oak, bears S.44°W., 13.8', scribed S29 T24S R4W
CS BT.
6" W.Oak, bears S.27°E., 16.9', scribed S28 T24S R4W
CS BT.
10" B.Oak, bears N.43°W., 12.3', scribed S28 T24S
R4W CS BT.
Note - Corner of a fence running West & South bears
S.51°W., 14.0'

Fd. & used in BLM dependent resurvey by James E. Jelly,
Cadastral Surveyor, under Group #979, surveyed May/Sept. 1979
(DCSO records Vol. 42 Page(s) 16397)

Harvey Christensen - For: Rosboro - 1/23/96 - M 123-36

Found - 1960 DCSO 2½" B.C.
BT's - 15" D.Fir, N.80°E., 8.7' healed face
10" Oak, S.27°E., 16.8' healed face
8" Oak, S.35°W., 13.4' healed face
12" Oak, N.39°W., 12.1' healed face

Fd. Ok by Templin - 6/1996 - M 125-36
Found OK by R. Brown, July 2001 - 2001-0075