

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855
(DCSO records Vol. 7 Page(s) 3046)

Set ¼ sec. post from which
 A B.Oak, 24" dia., bears S.65°E., 30 lks.
 A B.Oak, 8" dia., bears S.38°W., 32 lks.

Douglas Co. Surveyors Office -Milo E. Godfrey, Deputy Co.
Surveyor - Vernon Tracy - Mike Stone - April 1963 - C.S. File
53/9

No trace found.

Douglas Co. Surveyors Office - Larry Monrean - Randy Smith -
5/17/1989 - C.S. File 62/63-14

NOT FOUND
1¾ dia., axle 1' above ground leaning 0.7' south with a 5½"
dia., flange. flange has been stamped "965" (see rubbing in
file). We have found no record of a survey setting this
object as a quarter corner or any other survey point. Axle is
± 35' south of a random fence running easterly & westerly.
Axle is 300 to 400 feet easterly of NE cor. DLC 40 and 100 to
200 feet westerly of canyon bottom (and cat road). Running
generally northerly & southerly.