

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855 (DCSO records Vol. 7 Page(s) 3047)  
-----  
Set ¼ sec. post from which  
    A W.Oak, 10" dia., bears N.20°E., 27 lks.  
    A Laurel, 3" dia., bears N.18°W., 31 lks.

Douglas Co. Surveyors Office -Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy - Mike Stone - Feb. 18, 1963 - C.S. File 53/9-55  
-----  
Reported as not found.  
Fd. steel fence post & yellow tag indicating ¼ cor. - tag signed "R.L.M." Put up July 1961 - No BTs fd.

BLM dependent resurvey by James E. Jelly, Cadastral Surveyor, under Group #979, surveyed May/Sept. 1979 (DCSO records Vol. 42 Page(s) 16399-400)  
-----  
Point for the ¼ sec. cor. of secs. 8 & 9, at proportionate dist; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:  
                                  T24S R4W  
  ¼  
  S8 | S9  
  1979  
from which  
    A Basalt boulder, 6x6x5' above ground, bears N.53½°E., 33½ lks., mkd: X BO on W face.  
    A Fir, 6" dia., bears S.½°W., 12 lks.

Fd. & used in BLM dependent resurvey by Lance J. Bishop & James L. White, Cadastral Surveyor, under Group 1233, surveyed Oct. 1984/Jan. 1985 (DCSO records Vol. 47 Page(s) 18029)