

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor Secs 4, 5, 8, & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855
(DCSO records Vol. 7 Page(s) 3047)

Set post cor. from which
A Laurel, 8" dia., bears N.60°W., 45 lks.
A Laurel, 3" dia., bears S.18°W., 90 lks.
A Maple, 4" dia., bears S.80°E., 17 lks.
A Fir, 40" dia., bears N.40°E., 52 lks.

Douglas Co. Surveyors Office -Milo E. Godfrey, Deputy Co.
Surveyor - Vernon Tracy - Mike Stone - Feb/March 1963 - C.S.
File 53/9-24

Found - 14" Laurel, S.18°W., 59.4', (slope dist.) Cut open
& found unmistakable but illegible reverse
scribing.
60" Fir, N.40°E., 34.3', (slope dist.) shows scar.
Clump of small Maples S.80°E., 11.2'. Did not find
NW tree.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS OFFICE 1963
T24S R4W S5|S4
S8|S9
Rescribe 60" Fir, N.40°E., 34.3' (slope dist.) Mkd:
T24S R4W S4 CS BT
7" D.Fir, S.14°E., 36.0', mkd: T24S R4W S9 CS BT
7" D.Fir, S.61°W., 25.7', mkd: T24S R4W S8 CS BT
28" D.Fir, N.78W., 25.0', mkd: T24S R4W S5 CS BT
A steel fence post set for approx. cor. bears s.12°E., 35.8'
Corner lies on precipitous very rocky slope, just below
nearly perpendicular rock cliff 100' high. Cut cross 6x6" in
base of cliff 36.2' East of cor.

Fd. & used in BLM dependent resurvey by James E. Jelly,
Cadastral Surveyor, under Group #979, surveyed May/Sept. 1979
(DCSO records Vol. 42 Page(s) 16400)

Fd. & used in BLM dependent resurvey by Lance J. Bishop &
James L. White, Cadastral Surveyor, under Group 1233,
surveyed Oct. 1984/Jan. 1985 (DCSO records Vol. 47 Page(s)
18026-27)