

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 340540

PRIMARY CORNER DESCRIPTION C 1/4 Sec. 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM dependent resurvey by Lance J. Bishop & James L. White, Cadastral Surveyor, under Group 1233, surveyed Oct. 1984/Jan. 1985 (DCSO records Vol. 47 Page(s) 18028)

-----  
Point for the center ¼ sec. cor. of sec. 9, at intersection with the E. & W. center line.

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd: T24S R4W

C ¼  
S9  
1984

from which

A Fir, 5" dia., bears N.52°E., 15 lks. mkd: X BT.

A Fir, 6" dia., bears S.70°W., 14 lks. mkd: C¼ S9 BT.

David Edwards - Crew: Brant Miller & Eric Sprinkle -  
1/30/2017 - C.S. File 65/95-25

-----  
Found - BLM brass capped iron pipe in good condition.  
16" dia. Fir with healed blaze bears N.52°E., 9.9 ft  
18" dia. Fir stump, recently cut and used for a  
tailholt, bears S.70°W., 9.2 ft.

New - 19" dia., Fir scribed "C ¼ S9 BT" bears S.14°E.,  
29.46 ft to a 16d nail driven side-center at root  
crown.  
Decl. 15° East.