

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 343700

PRIMARY CORNER DESCRIPTION So. 1/4 cor. for Sec. 33 only, T23-4

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 6 Page(s) 2273)

-----  
Set ¼ sec. post, from which  
A Maple 10" dia., bears S.47°E., 31 lks. dist.  
A Maple 8" dia., bears N.35°W., 9 lks. dist.

Douglas County Surveyors Office - Milo E. Godfrey, Deputy -  
March 22, 1963 - C.S. File 53/9-55

-----  
Looked for, not found.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under  
Group #895, surveyed 1976 - (DCSO records Vol. 41 Page(s)  
16133-34)

-----  
Point for the ¼ sec. cor., at proportionate distance; there  
is no remaining evidence of the original corner.  
Seat a brass tablet, 3¼" dia., 3½" stem, in drill hole, in  
rock ledge, at base of small bluff, facing NW., with top mkd.  
T 23 S R 4 W  
    ¼ S 33  
T 24 S R 4 W  
    1976

from which  
A Maple 15" dia., bears N.19½°E., 58 lks. dist. mkd. ¼ S33  
BT.  
A Fir 22" dia., bears N.5½°W., 75 lks. dist. mkd. ¼ S33  
BT.

Survey by Daniel Baker - For: Weyerhaeuser Co. - Sept. 1994  
-M 119-38

-----  
Found - 3¼" US BLM brass cap dated 1976.  
24" Fir N.5°W., 49.5 ft. (Rec. N.5½°W., 75 lks.  
23" Maple S.89°E., 47.0 ft., closed face, record  
unknown.

Fd. OK by D. Baker, Nov. 1999 - M132-20

Fd. & use on BLM Dependent resurvey by Timothy J. Moore,  
Cadastral Surveyor & Robert Browning, Surveying Technician  
under Group #1955, surveyed 2000/2001 (DCSO rec. Vol. 54  
pg(s) 20889)

continued next page

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 343700

PRIMARY CORNER DESCRIPTION So. 1/4 cor. for Sec. 33 only, T23-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2168, Surveyed May/Nov. 2007 - DCSO records Vol. 57 Page(s) 22587

-----  
The ¼ sec. cor. of sec. 33 only on the S. bdy. of the Tp., monumented with a brass tablet, firmly set, flush with rock ledge, (properly) mkd.

from which the remaining bearing tree mkd. by Jelley in 1976

A fir, 29" dia., bears N.7°W., 49.4 ft., with a healed blaze. (Record; N.11¼°W., 50.6 ft.)

and a bearing tree not of record

A maple, 21" dia., bears N.87¼°E., 46.1 ft., with a healed blaze.