

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 33 & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855  
(DCSO records Vol. 7 Page(s) 3038)  
-----  
Set ¼ sec. post from which  
    A Fir, 24" dia., bears N.30°E., 38 lks.  
    A Laurel, 10" dia., bears N.25°W., 56 lks.

Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy - Mike Stone - May 1963 - C.S. File 53/9-89  
-----  
Found - Old 24" Fir snag, rotten & badly charred, N.30°E., 25.1', 2 old charred faces visible, faint scribing "BT" visible on lower face & part of "4" visible on upper face.  
    No trace of NW BT.  
Set - Brass cap at cor. mkd: COUNTY SURVEYOR'S OFFICE, 1963 T24S R4W ¼ S33/S34  
    24" D.Fir S.25°E., 25.8', mkd: ¼ S34 CS BT  
    26" D.Fir S.28°W., 38.3', mkd: ¼ S33 CS BT  
The N. end of a fence line running approx. South, is fastened to the SE BT, old timber in SW quad. All other directions have been logged off.

Fd. & used in BLM dependent resurvey by James E. Jelly, Cadastral Surveyor, under Group #979, surveyed May/Sept. 1979 (DCSO records Vol. 42 Page(s) 16383-84)

Fd. & used in BLM dependent resurvey by Lance J. Bishop & Wayne L. Rogers, Cadastral Surveyors, under Group #1178, surveyed Sept. 1983 (DCSO records Vol. 46 Page(s) 17810)

FD ok by H.Christensen 12/95, M 123-21