

PRIMARY CORNER DESCRIPTION Cor Secs 21, 22, 27 & 28

Alias 042020 Description NW Cor James Weaver DLC #42
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855
(DCSO records Vol. 7 Page(s) 3040)

Set post cor. for cor. from which
 A W.Oak, 12" dia., bears S.72°W., 81 lks.
 A W.Oak, 10" dia., bears N.20°W., 58 lks.
 A W.Oak, 10" dia., bears N.39°E., 73 lks.
 A W.Oak, 20" dia., bears S.72°E., 278 lks.

Gene Richardson & Edwin Woodford - 1945 - No record source

Set - ¾" by 36" I.P.
 3 old BTs still standing:
 20" W.Oak, S.72°E., 278 lks.
 10" W.Oak, N.20°W., 58 lks.
 10" W.Oak, N.39°E., 73 lks.

Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy - Mike Stone - May 1963 - C.S. File 53/9-65

Found - ¾" IP, set in 1945
 18" W.Oak, N.20°W., 38.3', has been opened, probably 1945. Faint scribing visible on badly rotted face.
 20" W.Oak, N.39°E., 48.2', faint scar visible, did not open.
 Down & party rotted Oak log, S.72°W., 53.5', cut open & found good reverse scribing, BT.
 34" W.Oak, S.72°E., 183.5', shows very plain axe scar. Didn't open.
 IP at corner in good condition extends 19" above surface of ground.
New BTs- 9" W.Oak, N.4°E., 56.1', mkd: T24S R4W S22 CS BT
 7" W.Oak, N.53°W., 22.0', mkd: T24S R4W S21 CS BT
 8" B.Oak, S.61°W., 24.8', mkd: T24S R4W S28 CS BT
 8" W.Oak, S.38½°E., 36.3', mkd: T24S R4W S27 CS BT

Fd. Ok by H. Christensen - 12/95 - M 123-21

Douglas Co. Surveyors Office - Stephen J Flauser - Mike Koch - 3/11/2015 - C.S. File 67/42-19

Found - A monument set in 1945 described as a ¾"x36" iron pipe is now a ¾" I.D. iron pipe that is loose, barely in ground and leaning. Top of pipe is damaged and rusted, when pipe is remove from ground (see monument set) it measures 27" long.
continued next page

