

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855 (DCSO records Vol. 7 Page(s) 3042)

-----

Set ¼ sec. post from which  
 A B.Oak, 15" dia., bears N.37°W., 53 lks.  
 A B.Oak, 24" dia., bears N.56°E., 80 lks.

BLM dependent resurvey by C. Albert White & Norman J. McDonald, cadastral surveyors, under Group #s 243, 350, & 513, surveyed April/July 1963 (DCSO records Vol. 32 Page(s) 13471-72)

The ¼ sec. cor. is determined at record distance from each of the OBTs:

- An Oak, dead & down, 30" dia., bears N.46°E., 80 lks., mkd. with old axe marks on rotted blaze. (Rec. bearing, N.56°E.)
- An Oak, 27" dia., bears N.41°W., 53 lks., with blaze healed. (Rec. bearing, N.37°W.)

At the corner point

Set an iron post, 28" long, 2½" dia., 21" in the ground, with brass cap mkd:

¼  
 S 16 | S 15  
 T24S R4W  
 1963

from which new bearing trees:

- A Fir, 15" dia., bears S.26°E., 26 lks., mkd: ¼ S15 BT.
- A Fir, 14" dia., bears S.78½°W., 15 lks., mkd: ¼ S16 BT.

Fd & used in BLM dependent resurvey by James E. Jelly, Cadastral Surveyor, under Group #979, surveyed May/Sept. 1979 (DCSO records Vol. 42 Page(s) 16387-88)

Douglas Co. Surveyors Office - Stephen J Flause - Mike Koch - 3/16/2015 - C.S. File 67/42-22

-----

Found - 1963 BLM 3¼" dia., brass cap (properly mkd) on a 2½" I.D. iron pipe firmly set leaning slightly south.  
 A B.Oak, 15" dia., now a 32" maple (previously misidentified as an Oak) with a partially rehealed blaze opening showing old axe marks inside; bears N.41°W., 35.0 ft (agrees with 1963 renewal meas) OBT  
 No evidence of NE OBT fd.  
 A fir, 15" dia., now a 35" dia., D.Fir with a fully healed single blaze; bears S.26°E., 16.0 ft. (rec. S.26°E., 17.2 ft.) 1963

continued next page

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 14" dia., now a 36"dia., D.Fir with a fully healed single blaze; bears S.78½°W., 9.9 ft. (as per record) 1963

New - A 10" dia. D.Fir scribed "¼ S15 CS" "BT" on a double blaze; bears N.6¾°E., 43.8 ft.

Note - Corner monument is near bottom of steep south slope, old reprod fir to west, young reprod fir in SE quad. New thinning partial-cut in NE quad. Compass decl. 15¼°E.