

PRIMARY CORNER DESCRIPTION Cor Secs 9, 10, 15, & 16

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Gordon & Gardner, Contract #52 dated Feb. 1855 (DCSO records Vol. 7 Page(s) 3042)  
-----  
Set cor. post from which  
A Fir, 10" dia., bears S.38°W., 173 lks.  
A Fir, 10" dia., bears S.10°E., 215 lks.  
A Fir, 30" dia., bears N.73°E., 238 lks.  
A Fir, 24" dia., bears N.70°W., 154 lks.

Original - Oscar F. Thiel, Contract #658, May 1896 (DCSO records Vol. 7 Page(s) 3065 & 3067 (dup.))  
-----  
I reestablish by setting a Fir post, 3' long, 4" sq., 24" in the ground mkd: T24S S10 on NE R4W S15 on SE; S16 on SW and S9 on NW faces with 4 notches on S and 3 notches on E edges and witnessed as described by the surveyor general.

Wilford Haines - Filed 2/17/1960 - C.S. File 51/67-1  
-----  
Found - 24" Fir, N.70°W., badly burnt.  
10" Fir, S.38°W., 175 lks., rotten stub, fd. scribe.  
30" Fir, N.73°E., 238 lks., down & burnt.  
SE BT not found.  
Set - 1"x1"x36" T iron.  
I.Cedar, N.6°E., 31.3'.

Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy - Mike Stone - May 1963 - C.S. File 53/9-30  
-----  
Found - Haines T iron & cap under log.  
12" I.Cedar N.6°E., 31.3', scribing all visible.  
Rotten Fir snag, now 24" S.38°W., 115'. Opened previously, good scribing visible on old face.  
54" Fir, N.70°W., 101.6', recently uprooted & down, old face badly burned.  
44" Fir stump, S.10°E., 141', edge of face scar visible on top of stump.  
Did not find NE BT  
DID NOT SET BRASS CAP  
New BTs- 21" D.Fir, S.56°E., 65.3', mkd: T24S R4W S15 CS BT.  
17" D.Fir, S.55°W., 46.3', mkd: T24S R4W S16 CS BT.  
9" W.Fir, N.58°W., 69.5', mkd: T24S R4W S9 CS BT.

PRIMARY CORNER DESCRIPTION Cor Secs 9, 10, 15, & 16

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM dependent resurvey by James E. Jelly, Cadastral Surveyor, under Group #979, surveyed May/Sept. 1979 (DCSO records Vol. 42 Page(s) 16388-89)

-----  
The cor. perpetuated by Haines & Godfrey, monumented with a T-shaped iron rod 1" dia., firmly set, projecting 4" above ground, from which the remains of an original bearing tree:  
A root hole, bears N.70°W., 154 lks., with a down Fir alongside, 48" dia., with fragmentary scribe marks visible on open blaze.

and a bearing tree mkd. by Haines  
A Cedar, 24" dia., bears N.6°E., 47½ lks., with healed blaze.

and the remains of bearing trees mkd: by Godfrey  
A Fir snag, 23" dia., bears S.56°E., 99 lks., with fragmentary scribe marks visible on open blaze.

A Fir stump, 22" dia., bears S.55°W., 70 lks., with healed blaze.

A Grand Fir, 20" dia., bears N.58°W., 105½ lks., with healed blaze.

At the corner point  
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

T24S R4W	
S 9	S 10
S 16	S 15
1979	

from which new bearing trees  
A Fir, 9" dia. bears S.55¼°E., 52 lks mkd: T24S R4W S15 BT  
A Fir, 11" dia. bears S.25°W., 7 lks. mkd: T24S R4W S16 BT  
Reset iron rod alongside iron post.

Fd. Ok by Troy Rambo, Aug. 2004 - M145-32