

PRIMARY CORNER DESCRIPTION 1/4 Cor. 9 & 10

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Oscar F. Thiel, Contract #658, May 1896 (DCSO records Vol. 7 Page(s) 3068)

Set a Fir post, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on the W face from which

- A Hemlock, 6" dia., bears N.50°W., 54 lks., mkd: ¼ S BT.
- A W.Fir, 16" dia., bears S.65°E., 65 lks., mkd: ¼ S BT.

Arthur R. Evens - For: Martin Bros. Box Co. - March 14, 1956 - C.S. File 42/207

Found - OBT, W.Fir snag, badly rotted, scribe plain.

Set - 3"x3"x48" Hemlock stake.

- 36" D.Fir, N.67½°W., 38.0', mkd: ¼ S9 RE 2741 BT. (Bark scribe - distance to center)
- 40" I.Cedar, S.59½°E., 59.8', mkd: ¼ S10 RE 2741 BT.

Yellow tag - "Grant and Evans" on NW BT.

Yellow FS location tag on OBT snag.

Wilford Haines - Filed 2/17/1960 - C.S. File 51/67-1

Found - 16" W.Fir, S.65°E., 65 lks.

- 6" Hemlock, down & rotten, fd scribe in rotten wood.
- 40" I.Cedar, S.65°E., 59.0',.
- 36" Fir, N.69°W., 39.0'

Scribed stake.

Set - 1"x1"x36" T iron.

Douglas Co. Surveyors Office -Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy - Mike Stone - Feb. & March 1963 - C.S. File 53/9-32

Found - Haines' "T" iron at corner.

- 36" Fir, N.67½°W., 38.0', recently uprooted & down, good bark scribing "T24". Evans 1956
- 40" I.Cedar, S.59½°E., 59.8', recently uprooted, lying face down. Evans 1956

Rotten remnants of W.Fir, S.65°E., 42.9'. All markings completely rotted away.

No trace of orig. NW tree.

DID NOT SET BRASS CAP

- New BTs- 4" Hemlock, N.42°E., 10.6', mkd: ¼ S10 CS BT.
- 5" Hemlock, S.48°W., 18.8', mkd: ¼ S9 CS BT.

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by James E. Jelly, Cadastral Surveyor, under Group #979, surveyed May/Sept. 1979 (DCSO records Vol. 42 Page(s) 16391)

The 1/4 cor. perpetuated & recorded by Evans in 1956 from orig. evidence no longer in existence, and further perpetuated & recorded by Haines in 1960, & further perpetuated & recorded by Godfrey in 1963, monumented with a T-shaped iron rod, 1" dia., firmly set, projecting 8" above ground, from which the remains of bearing trees mkd. by Evans:

A root hole, bears S.59 1/4°E., 90 1/2 lks., with a down Cedar alongside, 30" dia., no marks visible.

A root hole, bears N.67 1/2°W., 57 1/2 lks., with a down Fir alongside, 36" dia., no marks visible.

and bearing trees mkd. by Godfrey

A Hemlock, 11" dia., bears N.43°E., 16 lks., with healed blaze.

A Hemlock, 11" dia., bears S.46 1/2°W., 28 1/2 lks., with healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T24S R4W

1/4
S 9 | S 10

1979

Reset iron rod alongside iron post.

Fd. & used in BLM dependent resurvey by Lance J. Bishop & James L. White, Cadastral Surveyor, under Group 1233, surveyed Oct. 1984/Jan. 1985 (DCSO records Vol. 47 Page(s) 18028

Fd ok by S. Ness 6/25/1997 - C.S. File 65/15-4A

Troy Rambo - For: Seneca Jones Timber Co. - 8/2004 - M145-32

Found - 1979 BLM brass cap.

A 16" WH with a healed face - S.46 1/2°W., 28 1/2 lks.

The other record BT - now a low stump

Scribed- 1/4 S9 BT on a 16 DF - bears N.66°W., 21.2 ft.

1/4 S10 BT on a 12 DF - bears S.84E., 23.4 ft.

Nothing in the NE quadrant

Note - All new bearing trees were measured to a 6" spike at side center base. Bearings were measured with a hand compass with a declination of 17 east.