

PRIMARY CORNER DESCRIPTION C C for Secs. 3 & 4 only (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2168, Surveyed May/Nov. 2007 - DCSO records Vol. 57 Pages 22609-10

 True point for the closing cor. of secs. 3 and 4.
 Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, with brass cap mkd.
T23S R4W
 S 33
 S 4 | S 3
 C C
 T24S R4W
 2007

from which
 A hemlock, 6" dia., bears S.53¼°E., 3.4 ft., mkd. T24S R4W S3 CC BT.
 A cedar, 21" dia., bears S.79½°W., 33.0 ft., mkd. T24S R4W S4 CC BT.
 Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor., the closing cor. of secs. 3 & 4 bears N.0°39'02"W., 2.41 ft., perpetuated by Byron, in 1959, Godfrey, in 1963, monumented with an iron post, 1¼" dia., firmly set, projecting 15" above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T23S R4W S33 CC S4 S3 T24S 1959, from which the remains of the orig. bearing trees

A fallen, sawed, decayed fir stump, size indeterminate, bears S.56¾°E., 24.9 ft., with no marks visible. (Record, S.36°E., 23.1 ft.)
 A fir, 59" dia., bears S.1°W., 18.5 ft., with a healed blaze.
 and remains of a BT mkd. by Byron
 A fallen, sawed, decayed cedar stump, 8" dia., bears S.34½°W., 42.0 ft., with no marks visible. (Record, S.43°W., 34.6 ft.)
 and bearing tree mkd. by Godfrey
 A cedar, 37" dia., bears S.69°E., 62.0 ft., with a healed blaze.

Added the marks "AM" to the brass cap
 From this same cor., the cor. of secs. 33 and 34 only, T23S R4W bears S.89°59'32"E., 196.53 ft.