

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 15

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Oscar F. Thiel, Contract #658, May 1896 (DCSO records Vol. 7 Page(s) 3066)  
-----  
Set a Fir post 3' long, 3" sq. 24" in the ground for ¼ sec. cor. mkd: ¼ S, on N face from which  
    A Fir, 24" dia., bears N.63½°E., 13 lks., mkd: ¼ S BT.  
    A Fir, 20" dia., bears S.61°E., 23 lks., mkd: ¼ S BT.

Wilford Haines - Filed 2/17/1960 - C.S. File 51/67-1  
-----  
Found - 24" Fir, N.63½°E., 13 lks. (Stump)  
Set - 1"x1"x36" T-iron.  
Scribed- 16" D.Fir, S.23°W., 34.5'

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy - Mike Stone - Feb/Mar. 1963 - C.S. File 53/9-36  
-----  
Found - Haines T-iron at corner.  
    30" Fir stump, S.61°E., 15.2', scribing visible on partially opened face.  
    30" Fir stump, N.63½°E., 8.6', shows very plain axe scar.  
    18" Fir S.23°W., 34.5', bark scribing visible, also Haines' metal disc. nailed to tree.  
DID NOT SET BRASS CAP  
Corner lies on top of mall spur at top of steep N. slope.  
New BT - 7" Hemlock, N.46°W., 32.1', mkd: ¼ S10 CS BT.

BLM dependent resurvey by James E. Jelly, Cadastral Surveyor, under Group #979, surveyed May/Sept. 1979 (DCSO records Vol. 42 Page(s) 16389-90)  
-----  
The ¼ cor. perpetuated by Haines & Godfrey, monumented with a T shaped iron rod, 1" dia., firmly set, projecting 6" above ground, from which the remains of the OBTs:  
    A sawed Fir stump, 30" dia., bears N.63½°E., 13 lks., with fragmentary scribe marks visible on open blaze.  
    A sawed Fir stump, 30" dia., bears S.61°E., 23 lks., with fragmentary scribe marks visible on open blaze.  
and a bearing tree mkd. by Haines  
    A Fir, 20" dia., bears S.23°W., 52½ lks., dist., with fragmentary scribe marks visible on open blaze.  
and a bearing tree mkd. by Godfrey  
    A Hemlock, 10" dia., bears N.46°W., 48½ lks., with healed blaze.  
(Cont. next page)

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

At the corner point  
Set an iron post, 28" long, 2½" dia., 24" in the ground, with  
brass cap mkd: T24S R4W

¼  $\frac{S\ 10}{S\ 15}$

from which new bearing trees

A Fir, 6" dia., bears N.72½°W., 16½ lks., mkd: ¼ S10 BT.

A Fir, 5" dia., bears S.31¾°W., 16 lks., mkd: X BT.

Reset iron rod alongside iron post.

Fd. Ok by Troy Rambo, Aug. 2004 - M145-32