

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 10

Alias	Description

Original - Oscar F. Thiel, Contract #658, May 1896 (DCSO records Vol. 7 Page(s) 3069)

A point 50' below top of spur, I set a Fir post, 3' long, 3" sq., 24" in the ground for cor. mkd. ¼ S on N face from which

 A Fir, 6" dia., bears N.72°E., 35 lks., mkd: ¼ S BT.

 A Fir, 5" dia., bears S.81°W., 29 lks., mkd: ¼ S BT.

Wilford Haines - Filed 2/17/1960 - C.S. File 51/67-1

Found - 6" Fir, N.72°E., 35 lks.
 5" Fir, S.81°W., 29 lks.

Set - 1"x1"x36" T-iron.

Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy - Mike Stone - March/April 1963 - C.S. File 53/9-56

Found - Haines' "T" iron & cap.
 12" Fir, S.81°W., 19.1', previously opened, good scribing visible.
 17" Fir, N.72°E., 23.1', previously opened, good scribing visible.

New BTs- 15" D.Fir, N.18°E., 35.1', mkd: ¼ S3 CS BT.
 7" D.Fir, S.35°E., 40.6', mkd: ¼ S10 CS BT.

BLM dependent resurvey by Wayne L. Rogers, under Group #1834 surveyed April 1997 - (DCSO records Vol. 52 Page(s) 20182-3)

The ¼ sec. cor. of secs. 3 & 10, perpetuated by. Haines, in 1960, further perpetuated by Godfrey, in 1963; monumented with a "T" shaped iron rod, 1" diam., firmly set, projecting 4" above ground, with a brass washer mkd. Wilford N. Haines Survey Point Drain Or 239, from which the remains of the original bearing trees:

 A fir snag, 17" diam., bears N.75°E., 34 lks., with scribe mark T visible on reverse scribing. (Record, N.72°E., 35 lks.)

 A fir snag, 13" diam., bears S.82°W., 28 lks., with scribe marks ¼ S BT visible on opened blaze. (Record, S.81°W., 29 lks.)

and bearing trees mkd. by Godfrey

 A fir, 18" diam., bears N.18°E., 53 lks., with healed blaze.

 A fir snag, 8" diam., bears S.35°W., 60 lks., with healed blaze.

 At the corner point

continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 10

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Set a stainless steel post, 28" long, 2½" diam., 26" in the ground, directly over the T iron, with brass cap mkd.

T 24 S R 4 W
¼ S 3
 S 10
 1997

from which a new bearing tree

A fir, 4" diam., bears S.26°E., 36 lks., mkd. X BT.
Deposit a magnet in a white plastic case at the base of the stainless steel post.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2168, Surveyed May/Nov. 2007 - DCSO records Vol. 57 Page(s) 22606-7

The ¼ sec. cor. of secs. 3 & 10, monumented with an iron post, 2½" dia., firmly set, projecting 2" above ground, with brass cap (properly) mkd.

from which the remains of the orig. bearing trees
A decayed fir stump, size indeterminate, bears N.75°E., 22.4 ft., with no marks visible.
A decayed fir stump, 13" dia., bears S.82°W., 18.5 ft., with scribe marks ¼ S BT visible on wood fragment lying alongside.

and remains of BTs mkd. by Godfrey, in 1963
A fir snag, 17" dia., bears N.18°E., 35.0 ft., with a healed blaze.
A hollowed fir snag, 8" dia., bears S.36¼°E., 39.6 ft., with no marks visible. (Record, S.35°W.)

and bearing tree mkd. by Rogers
A fir, 10" dia., bears S.26°E., 23.8 ft., with a healed blaze.

and new bearing tree
A fir, 5" dia., bears N.24¾°E., 22.0 ft., mkd. ¼ S3 BT
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.