

TOWNSHIP 24 RANGE 4 POINT IDENTIFIER # 460400

PRIMARY CORNER DESCRIPTION E1/16 Secs. 15 & 22

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM dependent resurvey by James E. Jelly, Cadastral Surveyor, under Group #979, surveyed May/Sept. 1979 (DCSO records Vol. 42 Page(s) 16385)

-----  
Point for the E 1/16 sec. cor. of secs. 15 & 22  
Set an iron post, 28" long 2½" dia., 24" in the ground, with brass cap mkd.

E 1/16    S 15  
          S 22  
          1979

from which

An oak, 8" dia., bears N.45¼°E., 38 lks mkd: E 1/16 S15 BT  
A fir, 9" dia., bears S.67¾°E., 110 lks mkd: E 1/16 S22 BT

Douglas Co. Surveyors Office - Stephen J Flause - Mike Koch - 3/13/2015 - C.S. File 67/42-21

-----  
Found - 1979 3¼" dia., brass cap (properly mkd) on a 2½" I.D. iron pipe, firmly set protruding 2" above ground.

Corner falls in an E-W fence line.

An Oak 8" dia., now a 14" dia., B.Oak with a fully healed single blaze; bears N.45¼°E., 24.5 ft. (record N.45¼°E., 25.1 ft. is a slope dist.) 1979

A fir, 9" dia., now a 25" dia., x 2 ft. tall sawed D.Fir stump with a fully healed single blaze; bears S.67¾°E., 71.6 ft. (record S.67¾°E., 72.6 ft. is approx. slope dist.)

New - A 12" dia., W.Oak scribed "E1/16 S22" "CSBT" on a double blaze; bears S.48°E., 33.5 ft.

Note - Corner monument is in bottom of very shallow, westerly running draw. Dense Oak and Fir forest to north, clear-cut to south.

Compass decl. 15¼°E.