

PRIMARY CORNER DESCRIPTION CCC DLC 46; N-S centerline SE¼ Sec 15

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Donald Bentz - For: Knight Ranch - 11/1980 - M91-2 - (Map filed Jan. 1982)

Set - 5/8" iron rod from which:
 A 24" Fir bears S.54°E., 4.0 (BT)
 Corner is 23.5' north of fence line.

BLM dependent resurvey by James E. Jelly, Cadastral Surveyor, under Group #979, surveyed May/Sept. 1979 (DCSO records Vol. 42 Page(s) 16410)

The crossing closing cor. of the N. and S. center line of the SE¼ of sec. 15, with the N. bdy. of Claim No. 46, established and recorded by Bentz, in 1979, and is accepted as the corner, monumented with an iron rod, 5/8" dia., firmly set, projecting 4" above ground, from which a BT mkd. by Bentz:
 A fir, 23" dia., bears N.59¾°E., 6½ lks., with scribe marks BT visible on open blaze.

At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

E
CCC|S 15
 E
 DLC 46
 1979

from which a new bearing tree
 A fir, 15" dia., bears N.10½°W., 135 lks., mkd. T24S R4W S15 CCC BT.

Reset iron rod alongside iron post.

BLM resurvey by George M. Winter, Cadastral Surveyor under Group No. 2656, surveyed Sept./Nov. 2012 - (DCSO records Vol. 58 Page(s) 23010-1)

The crossing closing cor. of the N and S center line of the SE ¼ of sec. 15 and the N. bdy. of DLC 46, monumented with an iron post, 2½" dia., firmly set, projecting 2" above ground (alongside the iron post is a steel reinforcing rod, 5/8" dia., projecting 4" above ground), with brass cap (properly) mkd.

from which a bearing tree mkd. by Bentz, in 1979
 A fir, 34" dia. bears N.59¾°E., 4.3 ft with a healed blaze and a bearing tree mkd. by Jelly

A fir, 26" dia., bears N.10½°W., 89.1 ft. with a healed double blaze.

Corner is located 1 ft. W. of a fence extending N. and S. and 26 ft. N. of a fence extending E. and W.