

PRIMARY CORNER DESCRIPTION CCC DLC 46; E-W centerline SE¼ Sec. 15

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

BLM dependent resurvey by James E. Jelly, Cadastral Surveyor, under Group #979, surveyed May/Sept. 1979 (DCSO records Vol. 42 Page(s) 16416)

Point for the crossing closing cor. of the E. and W. center line of the SE¼ of sec. 15, with the E. bdy. of Claim No. 46. Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

DLC	S	CCC	S
46		S 15	
		1979	

from which

- A fir, 20" dia., bears N.58°E., 28 lks., mkd: T24S R4W S15 CCC BT.
- An oak, 8" dia., bears S.42°E., 47½ lks., mkd: T24S R4W S15 CCC BT.

BLM resurvey by George M. Winter, Cadastral Surveyor under Group No. 2656, surveyed Sept./Nov. 2012 - (DCSO records Vol. 58 Page(s) 23009-10)

The crossing closing cor. of the E. and W. center line of the SE¼ of sec. 15 and the E. bdy. of DLC 46, monumented with an iron post, 2½" dia., firmly set, projecting 7" above ground, with brass cap mkd.

from which bearing trees mkd. by Jelley in 1979

- A fir, 32" dia., bears N.58°E., 17.2 ft., with a healed blaze. (Record, 18.5 ft.)
- An oak, 10" dia., bears S.38½°E., 31.4 ft., with a healed blaze. (Record, S.42°E.)

Corner is located 4 ft. E. of a fence extending N. and S.