

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 500160

PRIMARY CORNER DESCRIPTION N 1/16 Cor. Secs. 34 & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Charles E. Akin, Jr., Cadastral Surveyor, under Group #793, surveyed Aug. 1972 (DCSO records Vol. 36 Page(s) 14856)

Point for the N 1/16 cor.
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:
 N 1/16
 S 34|S 35
 1972

from which
 A Fir, 17" dia., bears N.49½°E., 32 lks. mkd: N1/16 S35 BT
 A Fir, 17" dia., bears S.7½°W., 53 lks. mkd: N1/16 S34 BT

BLM dependent resurvey by Lance J. Bishop & James L. White, Cadastral Surveyor, under Group 1233, surveyed Oct. 1984/Jan. 1985 (DCSO records Vol. 47 Page(s) 18021-22))

Point for the N 1/16 cor.
From this point, the N 1/16 cor. erroneously est. by Akin bears S.8°30'E., 0.30 chs.
Remove the iron post, destroy the marks on the trees and at the true cor. point
reset the iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:
 N 1/16
 S 34|S 35
 1985
 1972

from which
 A Fir, 24" dia., bears S.26½°E., 64 lks. mkd: N1/16 S35 BT
 A Fir, 8" dia., bears S.83½°W., 128 lks. mkd: N1/16 S34 BT

Fd. & used by BLM dependent resurvey by Wayne L. Rogers & Boyd W. Peterson, Cadastral Surveyors, under Group #1314, surveyed April/May 1986 (DCSO records Vol. 48 Page(s) 18276)

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - Sept. 20, 1993 - C.S. File 64/47-4

Found - 3¼" dia., BLM BC, properly marked, on a 2½" IP, protrudes 3" above ground.
24" now 24" dia, D.Fir with a fully healed single blaze, bears S.28°E., 42.2'. (Rec. S.26½°E, 42.2')
1985 BLM
8" now 8" dia., dead 20' high D.Fir snag w/partially healed single blaze scribing vis. "N1/16 S34 BT" bears S.83½°W., 84.5', agrees w/rec. 1985 BLM
(Cont. next page)

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 500160

PRIMARY CORNER DESCRIPTION N 1/16 Cor. Secs. 34 & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set - 36" dia, 4' high D.Fir stump with boat spike set through BT tag on top, B.S. bears N.14°E., 104.8', boat spike is 8" long & stamped BO 2 on top.
3" dia, D.Fir, double blazed & scribed "X BT" bears N.43½°W., 42.9'.
23" dia., 5' high D.Fir stump with boat spike set through BT tag on top (has a chopped out blaze on SW trunk) BS bears S.74½°E., 19.6'. Boat spike is 8" long & stamped BO 1 top.