

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 540140

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

L.W. Barber - For: BLM - May 15, 1974 (Filed Nov. 1984) - M97-62

Set - Rebar, 1/2" x 18"
BTs - 14" Cedar, S.75°E., 7.5 ft.
 18" Cedar, S.36°30'W., 19.3 ft.

BLM dependent resurvey by Wayne L. Rogers & Boyd W. Peterson, Cadastral Surveyor, Group #1314, surveyed April/May 1986 (DCSO records Vol. 48 Page(s) 18271)

Point for the center 1/4 cor. at intersection with the E & W center line.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
 T 24 S R 4 W
 C 1/4
 S 35
 1986

from which
 A Fir, 6" dia., bears S.62°E., 21 lks., mkd. C 1/4 S35 BT.
 A Cedar, 10" dia., bears S.9 1/4°E., 31 lks., mkd. C 1/4 S35 BT.
Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

From this point , a point unofficially established by L.W. Barber, Federal Highway Administration, in 1974, bears S.13°11'E., 0.26 chs., monumented with an iron rod, 1/2" dia., firmly set, projecting 2" above ground.

FD. ok by Kris DeGroot, 8/2008 - 2008-0061A-G