

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855  
(DCSO records Vol. 7 Page(s) 3033)

-----

Set 1/4 sec. post from which  
 A Fir, 20" dia., bears N.44°W., 32 lks.  
 A Fir, 36" dia., bears S.14°E., 32 lks.

Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy - Mike Stone - June 10, 1963 - C.S. File 53/9-99

-----

Reported as not found.  
 Found 2 old firs - one down several years; one a stub - that could have been orig. BTs. Fd. old axe mks in both, but no scribing - mks could have been made by someone looking for cor.

BLM Resurvey by C. Albert White & Norman J. McDonald, Cadastral Surveyors, under Group #'s 243, 350, & 513, surveyed April/July 1963 - (DCSO records Vol. 32 Page(s) 13465)

-----

Point for the 1/4 sec. cor. of secs. 25 & 26, at proportionate distance; there is no remaining evidence of the original corner.  
 Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

	1/4	
S 26	S 25	
T 24	R 4 W	
	1963	

from which  
 A Hemlock, 12" dia., bears N.50°E., 71 lks. mkd: 1/4 S25 BT.  
 A Fir, 12" dia., bears S.21 1/2°W., 62 lks., mkd: 1/4 S26 BT.

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 8/10/1990 - C.S. File 64/10-3

-----

Found - A 3 1/4" dia., 1963 BLM brass cap on a 2 1/2" O.D. iron pipe, protruding 4" above ground.  
 12" now 16" dia., D.Fir with a fully healed single blaze bears S.21 1/2°W., 40.9' (Agrees w/rec.)  
 1963 BLM BT  
 12" now 14" dia., 4' high Hemlock stump with a fully healed single blaze, bears N.50°E., 46.9'.  
 (agrees w/rec.) 1963 BT

(Cont. next page)

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- 7" dia., pistol butt D.Fir, double blazed and scribed "¼ S26 CS BT" bears N.62°W., 22.2' to root crown.  
14" dia., Maple double blazed and scribed "¼ S25 CS BT" bears S.7,°E., 3.6'.

Fd. Ok by D.C.S.O. - 11/28/1995 - C.S. File 64/64-9  
FD. ok by Kris DeGroot, 8/2008 - 2008-0061A-G