

PRIMARY CORNER DESCRIPTION Cor. Secs. 13, 14, 23, & 24

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Gordon & Gardner, Contract #52 dated Feb. 1855 (DCSO records Vol. 7 Page(s) 3032)

Set post cor. of secs. 13, 14, 23, & 24 from which

- A Laurel, 15" dia., bears N.81°E., 53 lks.
- A Laurel, 12" dia., bears S.68°E., 80 lks.
- A Laurel, 3" dia., bears S.15°W., 24 lks.
- A Fir, 10" dia., bears N.60°W., 113 lks.

Original - Oscar F. Theil, Contract #658 dated May 1896 (DCSO records Vol. 7 Page(s) 3076)

The post for the cor. of secs. 13, 14, 23, & 24 being gone but the bearing trees remaining.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy - Mike Stone - Feb/March 1963 - C.S. File 53/9-25

Found - Laurel S.68°E., 52.8'. Tree broken off near ground, cut open & found good reverse scribing (old) "S"
Laurel N.81°E., 35.0'. Tree alive, but S. side & entire center of tree rotted & burned away. Fairly recent scribing on both Laurels.
No trace of SW or NW trees

Set - Brass cap at cor. mkd: County Surveyor's Office
1963 T24S R4W S14 | S13
 S23 | S24

New BTs- 5" D.Fir N.38°W., 8.4', mkd: S14 CS BT.
16" D.Fir S.8°E., 8.4', mkd: T24S R4W S24 CS BT.
7" D.Fir N.60°E., 30.7' mkd: T24S R4W S13 CS BT.
6" Madrone S.43°W., 50.4' mkd: T24S R4W S23 CS BT.

BLM dependent resurvey, Boyd W. Peterson, Group #1511, Surveyed Nov. 1989 thru May 1990 (DCSO records Vol. 50 Page(s) 19003)

At the cor., perpetuated by Godfrey in 1963, recorded in Douglas County Surveyors Office, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 5 ins. above ground, with brass cap properly mkd. from which an original bearing tree

- A madrone, 24 ins. diam., bears N.81°E., 54½ lks., no marks visible. (Record, 53 lks.)

(Cont. next page)

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Cor. Secs. 13, 14, 23, & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and bearing trees mkd. by Godfrey
A fir, 16 ins. dia., bears N.60°E., 46½ lks., with healed blaze.
A fir, 22 ins. dia., bears S.8°E., 13½ lks., with healed double blaze.
A madrone, 11 ins. dia., bears S.43°W., 77 lks., with healed blaze.
and a new bearing tree
A fir, 11 ins. diam., bears N.61°W., 34 lks., mkd. T24S R4W S14 BT.
The corner is located at fence corner, from which woven wire fences extend N., S., E., and W.

Fd. Ok by D. Edwards, 7/2008 - 2008-0066A&B