

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Original - Gordon & Gardner, Contract #52 dated Feb. 1855  
(DCSO records Vol. 7 Page(s) 3032)

-----

Set 1/4 sec. post from which  
 A Dogwood, 4" dia., bears N.26°W., 6 lks.  
 A Redwood, 36" dia., bears S.46°E., 18 lks.

Douglas Co. Surveyors Office -Milo E. Godfrey, Deputy Co.  
 Surveyor - Vernon Tracy - Mike Stone - July 1963 - C.S. File  
 53/9-20

-----

Reported as not found.  
 Fd. small fir blazed on 4 sides on N & S blazed line. No BTs  
 fd.

BLM dependent resurvey, Boyd W. Peterson, Group #1511,  
 Surveyed Nov. 1989 thru May 1990 (DCSO records Vol. 50  
 Page(s) 19003-4)

-----

Point for the 1/4 sec. cor. of secs. 13 & 14, at proportionate  
 distance; there is no remaining evidence of the original  
 corner.  
 Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20  
 ins. in the ground, with brass cap mkd.

T 24 S R 4 W

S 14 <sup>1/4</sup> S 13

1989

from which  
 A fir, 10 ins. diam., bears N.77°E., 5 lks. dist., mkd.  
 1/4 S13 BT.  
 A fir, 31 ins. diam., bears S.17°W., 43 lks. dist., mkd.  
 1/4 S14 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the  
 stainless steel post.  
 From this point, the BLM Geodetic Control Station No. EC  
 41055, at latitude 43° 29' 10.275" N., longitude 123° 07'  
 10.530" W. (NAD 1927), determined by NAVSTAR Global  
 Positioning System, bears N. 60° 22' 59" E., 32.730 chs.  
 dist., monumented with an alum. rod, 72 ins. long, 3/4 in.  
 diam., set 72 ins. in the ground, with an aluminum cap mkd.  
 EC 41055 GPS 1990, and an orange carsonite post alongside.