

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855 (DCSO records Vol. 7 Page(s) 3031-32)

Set post cor. of secs. 11, 12, 13, & 14 from which

- A Fir, 20" dia., bears N.49°W., 38 lks.
- A Fir, 24" dia., bears N.50°E., 27 lks.
- A Redwood, 12" dia., bears S.68°E., 60 lks.
- A Redwood, 6" dia., bears S.10°W., 21 lks.

Original - Oscar F. Theil, Contract #658, May 1896 (DCSO records Vol. 7 Page(s) 3076 & 3064 (dup))

The post for cor. of secs. 11, 12, 13, & 14 being gone but the bearing trees remaining, I reestablish. On account of cutting in a bearing tree, I gave another

- A Hemlock, 14" dia., bears S.2 3/4°W., 82 lks.

GLO dependent resurvey by Lynn M. Roseberry, Cadastral Surveyor, Group #349, surveyed Aug/Sept 1957 (DCSO records Vol. 28 Page(s) 12099)

The cor. is perpetuated by a cedar stake, 3' long, 2" square, firmly set 12" in the ground from which the remaining original BTs:

- A Cedar, 32" dia., bears S.68°E., 60 lks., with scribe marks R4W visible on partly opened blaze. (Rec. calls for a redwood)
- A Cedar, 20" dia., bears S.11°W, 22½°lks., with a healed blaze. (Rec., a redwood, bears S.10°W., 21 lks.)
- A turned out Fir snag, 30" dia., bears N.49°W., 38 lks., with scribe marks S R4W visible on partly opened blaze.

At the corner point
Set an iron post, 30" long, 2" dia., 24" in the ground, with brass cap mkd:

T24S R4W	
S 11	S 12
S 14	S 13
1957	

from which

- A Fir, 17" dia., bears N.18°E., 29 lks., mkd: T24S R4W S12 BT.
- A Fir, 27" dia., bears N.7°W., 104 lks., mkd: T24S R4W S11 BT.

Reset the cedar stake alongside the iron post.

PRIMARY CORNER DESCRIPTION Cor. Secs 11, 12, 13, & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____


Douglas Co. Surveyors Office -Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy - Mike Stone - Feb/March 1963 - C.S. File 53/9-39

Found - GLO brass cap set in 1957.
 32" Cedar S.68°E., 39.6', alive & in good condition, scribing visible.
 20" Cedar S.11°W., 14.8', alive & in good condition, shows scar.
 27" Fir, N.7°W., 68.9', alive & in good condition, scribing all vis., scar not healed over.
 17" Fir, N.18°E., 19.1', is now dead, scribing vis.

Reblaze & scribe:
 32" Cedar, S.68°E., 39.6', mkd: T24S R4W S13 CS BT.
 20" Cedar S.11°W., 14.8', mkd: T24S R4W S12 CS BT.
 New BT - 10" D.Fir, N.80°E., 76.2', mkd: T24S R4W S12 CS BT.

BLM dependent resurvey, Boyd W. Peterson, Group #1511, Surveyed Nov. 1989/May 1990 (DCSO recs Vol. 50 Pg 19003-4)

The cor. is monumented with an iron post, 2½" diam., firmly set, projecting 8" above ground, with brass cap mkd.



from which the remains of original bearing trees

- A cedar, 40 ins. diam., bears S. 68° E., 60 lks. dist., with fragmentary scribe marks visible on partially healed double blaze.
- A sawed cedar stump, 24 ins. diam., bears S. 11° W., 22½ lks. dist., with healed double blaze.
- A root hole, bears N. 49° W., 38 lks. dist., with a down, rotted cedar alongside, size indeterminate, no marks visible.

and a bearing tree mkd. by Roseberry

- A fir, 35 ins. diam., bears N. 7° W., 104 lks. dist., with healed blaze.

and a bearing tree mkd. by Godfrey in 1963,

- A fir, 21 ins. diam., bears N. 78° E., 118 lks. dist., with healed blaze.

and a new bearing tree

- A fir, 10 ins. diam., bears S. 74° W., 31 lks. dist., mkd. T24S R4W S14 BT.

Fd. Ok by D. Edwards, 5/2006 - C.S. File 65/57-9