TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855 (DCSO records Vol. 7 Page(s) 3031)

Set ¼ sec. post from which
A Cedar, 8" dia., bears N.40°W., 15 lks.
A Yew, 6" dia., bears N.23°E., 54 lks.

Original - Oscar F. Theil, Contract #658, May 1896 (DCSO records Vol. 7 Page(s) 3074)

The ¼ sec. cor., a Fir post 24" above ground firmly set, but badly decayed, marked & witnessed as described by the Surveyor General and which I replace at the same point, by setting a Fir post, 3' long 3" sq. 24" in the ground for ¼ Sec. cor. marked ¼ S on W face, having destroyed all remains of the old post.

GLO dependent resurvey by Lynn M. Roseberry, Cadastral Surveyor, Group #349, surveyed Aug/Sept 1957 (DCSO records Vol. 28 Page(s) 12099-100)

The ¼ sec. cor. of secs 11 & 12, at proportionate distance, there is no remaining evidence of the original corner.
Set an iron post, 30" long, 2" dia, 24" in the ground with brass cap marked: T24S R4W

¼

S 11|S 12

1957

from which
A Fir, 7" dia., bears S.31°E., 53½° lks., mkd: ¼ S12 BT.
A Hemlock, 8" dia., bears N.49½°W., 17 lks.,mkd: ¼ S11 BT.

Fd. Ok by D. Edwards, 5/2006 - C.S. File 65/57-9