

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 2

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Oscar F. Theil, Contract #658, May 1896 (DCSO records Vol. 7 Page(s) 3078)

-----  
Set a basalt stone 12x10x6 ins., 8" in the ground for ¼ sec. cor. mkd: ¼ on W face from which  
A Laurel, 7" dia., bears S.46°E., 57 lks., mkd: ¼ S BT.  
A Laurel, 8" dia., bears S.78°W., 21 lks., mkd: ¼ S BT.

-----  
GLO dependent resurvey by Lynn M. Roseberry, Cadastral Surveyor, Group #349, surveyed Aug/Sept 1957 (DCSO records Vol. 28 Page(s) 12101-02)

-----  
Point for the ¼ sec. cor., at proportionate dist; there is no remaining evidence of the orig. corner.  
Set an iron post, 30" long, 2" dia., 16" in the ground, to solid rock and in a mound of stone, 2' base, to top, with brass cap mkd:

T24S R4W  
¼  
S 2 | S 1  
1957

from which  
A Fir, 26" dia., bears N.42°E., 14½ lks., mkd: ¼ S1 BT.  
A Fir, 7" dia., bears S.47°W., 50 lks., mkd: ¼ S2 BT.

-----  
BLM rehabilitation of certain corners, Timothy J. Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech., under Group #2000, Surveyed May 2002/May 2003, - (DCSO records Vol. 54 Page(s) 21115-6)

-----  
The ¼ sec. cor. of secs. 1 and 2, monumented with an iron post, 2½" dia., firmly set, projecting 9" above ground, with brass cap (properly) mkd.

from which the remains of bearing trees mkd. by Roseberry  
A sawed fir stump, 24" dia., bears N.37°E., 9.6 ft., with a healed blaze. (Record, N.42°E.)  
A fir, 17" dia. bears S.46½°W., 33.0 ft. with a healed blaze. (Record, S.47°W.)

and a new bearing tree  
A fir, 9" dia., bears S.¼° E., 26.2 ft., mkd. ¼ S1 BT  
Corner is located on a rock shelf, 5 ft. above the base of a rock bluff, 25 ft. tall.

The geographic position (NAD 1983) of this cor., determined by a direct occupation, utilizing a resource mapping grade GPS receiver, (GEO Explorer 3), differentially corrected, is as follows:

Latitude: 43°30'49.7"N. Longitude: 123°07'39.8"W.