

TOWNSHIP 24 RANGE 04 POINT IDENTIFIER # 620200

PRIMARY CORNER DESCRIPTION West 1/16 corner Secs. 25 & 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM Resurvey by C. Albert White & Norman J. McDonald, Cadastral Surveyors, under Group #'s 243, 350, & 513, surveyed April/July 1963 - (DCSO records Vol. 32 Page(s) 13463)

-----  
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd: W 1/16  $\frac{S\ 25}{S\ 36}$   
1963

from which

- A Fir, 27" dia., bears N.78½°W., 9 lks.
- A Fir, 14" dia., bears S.31 3/4°E., 28 lks.

Douglas Co. Surveyors Office - John Powell & Crew - Oct. 1970 - C.S. File 53/9-2

-----  
Found - 1963 BLM brass cap, properly mkd.  
28" D.Fir, N.78½°W., 5.9', pitched over, scribe vis.  
(This tree to be cut, high stump)  
29" D.Fir, S.32°E., 18.5', pitched over, scribe vis.  
New BT - 18" double Cedar, N.15°W., 42.6', scribed "W 1/16 S25 CS BT"  
New BO - 5/8" I. Rod at the base of 30" D.Fir stump N.20°E., 39.1'.